


Panel mounted inlet

Part no. 3531




- screw terminals
- with protective cover

Technical specifications

Ampere	16 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP67
Weight	212 g
Certifications	VDE, EAC

Drawing



Drawing 2 MB 62	Amp.	16			32			63		
		Poles			Poles			Poles		
Dim. in mm	a	85	85	85	85	85	108	108	108	
	b	85	85	85	85	85	101	101	101	
	c	132	132	131	131	137	164	164	164	
	d	70	70	70	70	70	85	85	85	
	e	70	70	70	70	70	77	77	77	
	f	6.3	6.3	6.3	6.3	6.3	6.5	6.5	6.5	
	g.	11	11	11	11	11	12	12	12	
	g.1	2	2	2	2	2	2	2	2	
	h	100	107	108	108	111	130	130	130	
	s	70	87	94	94	102	114	114	114	
	l	30	30	30	30	30	40	40	40	
Terminal for cond. cross		1	1	2,5	2,5	2,5	6	6	6	
section (mm ²) min.-max.		-2,5	-2,5	-6	-6	-6	-16	-16	-16	