

## Wall mounted receptacle

Part no. 9530




- screw terminals
- [highly resistant to chemicals](#)
- highly heat resistant contact carrier
- nickel plated contacts
- two external fixing points
- enclosure can be turned 180°
- receptacles are designed for adding an auxiliary contact switch

## Technical specifications

Ampere	16 A
Poles	7 p
Voltage	230 V
Clock position	9 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	nickel plated contacts, highly heat resistant contact carrier
Protection type	IP67
Enclosure material	Plastic, high resistance to chemicals / AMELAN
Weight	213 g
Certifications	EAC

## Drawing



Drawing	Amp.	16	32
1 MB 622	Poles	7	7
Dim. in mm	a	100	100
	b	101	109
	c	131	160
	d	50	50
	e	84	92
	f1	5.3	5.3
	f2	5.3	5.3
	g	6.5	6.5
	h	132	148
	i	24.7	27.5
	M	25 (optional M20)	32 (optional M25)
M*	2x25 (blind) to be cut out	2x25 (blind) to be cut out	
Max. cable diam. (mm)	18 (M25) and 15 (M20)	25 (M32) and 18 (M25)	
Terminal for cond. cross section (mm <sup>2</sup> ) min.-max.	1.5	2.5	
	—4	—6	